



DUAL offers a virtual dual monitor that allows you to operate with maximum efficiency, having all informations under control and a fully Industry 4.0 compliance.



#### The beauty of technology

The new **DUAL** offers top level efficiency in press brakes programming and control. The winning Made in Italy design and the high quality of all the construction details, guarantee prestigious performances and a long product life.

### Smart virtual Dual Monitor

In the second virtual monitor area, you can view useful documents such as images, videos, PDFs or live webcam, which can also be loaded from your mobile device, and visible and accessible during production. What is traditionally used as a paper support (drawings of the piece, specific details of the tooling or production sequence) becomes multimedia content available on the upper screen.

### Fully Industry 4.0 compliance

It's **Industry 4.0 Ready** thanks to the production and maintenance management and support for remote programming and supervision. Machine status monitoring through cloud reporting and system integration into a smart factory, through support for the *MTConnect* industrial communication standard and *IoT* support through *MQTT* protocol.



#### Features

#### • INDUSTRY 4.0 READY Production management and scheduling

- Scheduled Maintenance Management for a machine always efficient
- IoT support through MQTT protocol
- Advanced programming assisted by attachments and video
- Sampling of the material for an accurate production
- Exporting of computed flat patterns as DXF files
- Tools and parts import from CAD (DXF and IGES/STEP on Advanced 3D)
- 3D Simulation with automatic best bend sequence identification with collision detection
- Automatic tool selection and machine tooling
- TeamViewer for Remote assistance
- Linux OS

#### **Technical specification**

| RAM       | DDR3 4Gb                                 |
|-----------|--|
| Supply    | 24Vdc                                    |
| Monitor   | Colours LCD TFT, Capacitive Touch-screen |
| Hard Disk | M.2 SSD 128 GByte                        |
| USB       | 4 ports 3.0                              |
| Net Card  | 2 Gigabit Ethernet RJ-45                 |
| Power     | 36W (1.5A - 24Vdc)                       |

#### **Software Levels**

| Standard 3D | 3D editor and simulation, DXF parts import    |
|-------------|---|
| Advanced 3D | Add to Standard 3D the IGES/STEP parts import |

| Model    | Software    | Standard axes |
|----------|-------------|---------------|
| DUAL 22  | Standard 3D | 12            |
| DUAL 22+ | Advanced 3D | 12            |
| DUAL 27  | Standard 3D | 12            |
| DUAL 27+ | Advanced 3D | 12            |



Motion is the modular units that STEP designed to interface and control all types of press brakes: hydraulics, electrical and hybrids.

## **Everything under control**

It's equipped with a PLC logic with a lot of inputs/outputs. The numerical control, connected through Can Bus interface to one or more **Motion** modules, is able to completely manage the machine.

- Motion3 is the compact module able to drive up to 3 axes.
- Motion4 is the standard module able to drive 4 axes.
- Motion4+ is the All in One solution which includes the digital amplifier board for the direct interface of the proportional valves.

|                                   | Motion3                                   | Motion4 / Motion4+                        |
|-----------------------------------|---|---|
| Serials                           | n° 1 USB + n° 1 Canbus                    | n° 1 USB + n° 1 Canbus                    |
| Digital Inputs/Outputs            | 12 inputs 24Vdc - 12 outputs 24Vdc        | 24 inputs 24Vdc - 24 outputs 24Vdc        |
| Encoders interface                | 3 inputs for incremental encoders (+5Vdc) | 4 inputs for incremental encoders (+5Vdc) |
| Analogical Inputs/Outputs         | 2 analog inputs ±10V                      | 4 analog inputs ±10V                      |
|                                   | 3 analog output ±10V to control 3 axes    | 4 analog output ±10V to control 4 axes    |
| Dueseume / Organization controle  | 2 analog outputs (0-10) V                 | 2 current outputs 0÷4A (standard 2A)      |
| Pressure / Crowning controls      |   | 2 analog outputs (0-10) V                 |
| Volues Interface (only Mation 4.) | -   | Double Valves connections for Y1 and Y2   |
| Valves Interface (only Motion4+)  |   | LVDT feedback interface                   |
| Dimensions (HxWxD)                | 270 x 27 x 100 mm                         | 270 x 50 x 100 mm                         |



# STEP AUTOMATION SRL

Via Manzoni, 36 - 24060 San Paolo D'Argon (BG) - ITALY Phone: +39 035 4254492 - Fax: +39 035 4253971 E-mail: info@stepautomation.it www.stepautomation.it

